

60,469-092 PUS1
PA-000.05193-USRECEIVED
CENTRAL FAX CENTER

DEC 05 2007

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A method of modeling a condition of an elevator tensile support, comprising;
 - determining a rate of degradation of the tensile support for a selected load;
 - modeling a configuration of at least one selected elevator system;
 - estimating an elevator traffic pattern;
 - determining sheave contact and load information using ~~the determined rate of degradation,~~ the modeled configuration and the estimated traffic pattern; and
 - determining a mean degradation of the tensile support from the determined rate of degradation and the determined sheave contact and load information.
2. (Original) The method of claim 1, including determining a plurality of mean degradation values by varying at least one of the modeled configuration or the estimated elevator traffic pattern.
3. (Original) The method of claim 1, including determining a relationship between an electrical characteristic and a selected condition of the tensile support and using the determined relationship and the determined mean degradation for determining an apparent electrical characteristic value corresponding to the selected condition of the tensile support.
4. (Original) The method of claim 3, including repeatedly performing the steps of claim 3 to determine a plurality of the apparent electrical characteristic values and using the values to determine a relationship between a corresponding measured electrical characteristic and a condition of a tensile support.
5. (Original) The method of claim 4, wherein the electrical characteristic is resistance.

60,469-092 PUS1
PA-000.05193-US

6. (Original) The method of claim 5, including subsequently measuring a resistance of a tensile support and using the determined relationship between resistance and the selected condition of the tensile support to determine a current condition of the tensile support.
7. (Previously Presented) The method of claim 1, including
generating a first map from the determined mean degradation;
generating a second map correlating an electrical characteristic with a selected degree of strength degradation;
combining the first and second maps to generate a third map correlating the electrical characteristic with a remaining strength in the tensile support.
8. (Previously Presented) The method of claim 7, wherein the step of generating the first map comprises incorporating at least one tensile support operational factor with the determined rate of degradation.
9. (Original) The method of claim 8, wherein said at least one tensile support operational factor is selected from the group consisting of an elevator system configuration, estimated elevator traffic, actual elevator usage, and sheave contact.
10. (Previously Presented) The method of claim 9, wherein said at least one tensile support operational factor is the actual elevator usage, and wherein the step of generating the first map further comprises using an updated actual elevator usage.
11. (Original) The method of claim 7, wherein the combining step comprises:
generating an intermediate map that correlates the electrical characteristic with remaining strength in a segment of the tensile support, wherein the tensile support comprises a plurality of segments; and
summing the remaining strengths of the plurality of segments to generate the third map.
12. (Original) The method of claim 7, comprising incorporating a degradation rate variance factor in the first map.

60,469-092 PUS1
PA-000.05193-US

13. (Original) The method of claim 7, comprising incorporating an electrical characteristic variance factor in the second map.
14. (Original) The method of claim 7, comprising incorporating at least one of a temperature-induced variance factor and an electronic device variance factor to generate the third map.
15. (Original) The method of claim 7, wherein the electrical characteristic is resistance.
16. (Currently Amended) A system for determining a condition of an elevator tensile support, comprising:
a device for measuring an electrical characteristic of at least a portion of the tensile support; and
a controller that determines a current condition of the tensile support by relating the measured characteristic to a predetermined data set indicating a relationship between corresponding apparent characteristic values and conditions of the tensile support, the relationship being based upon at least one of a determined rate of degradation of the tensile support for a selected load, a modeled configuration of an elevator system, an estimated elevator traffic pattern, ~~sheave contact and load information~~, or a mean degradation of the tensile support based upon determined sheave contact and load information.
17. (Currently Amended) The system of claim 16, wherein the controller
determines a rate of degradation of the tensile support for a selected load;
models a configuration of at least one selected elevator system;
estimates an elevator traffic pattern;
determines sheave contact and load information using ~~the determined rate of degradation~~, the modeled configuration and the estimated traffic pattern; and
determines a mean degradation of the tensile support from the determined rate of degradation and the determined sheave contact and load information.

60,469-092 PUS1
PA-000.05193-US

18. (Original) The system of claim 17, wherein the controller determines a relationship between an electrical characteristic and a selected condition of the tensile support and uses the determined relationship and the determined mean degradation for determining an apparent electrical characteristic value corresponding to the selected condition of the tensile support.

19. (Original) The system of claim 18, wherein the controller determines a plurality of the apparent electrical characteristic values and uses those values to determine a relationship between a corresponding measured electrical characteristic and a condition of a tensile support.

20. (Original) The system of claim 16, wherein the electrical characteristic is resistance.

21. (Currently Amended) A controller useful for determining a condition of an elevator tensile support, comprising:

a storage medium containing programming for
_____determining a rate of degradation of the tensile support for a selected load;
modeling a configuration of at least one selected elevator system;
estimating an elevator traffic pattern;
determining sheave contact and load information using ~~the determined rate of degradation,~~ the modeled configuration and the estimated traffic pattern; and
determining a mean degradation of the tensile support from the determined rate of degradation and the determined sheave contact and load information.

22. (Original) The controller of claim 21, including programming for determining a plurality of mean degradation values by varying at least one of the modeled configuration or the estimated elevator traffic pattern.

23. (Original) The controller of claim 21, including programming for determining a relationship between an electrical characteristic and a selected condition of the tensile support and using the determined relationship and the determined mean degradation for determining an apparent electrical characteristic value corresponding to the selected condition of the tensile support.

60,469-092 PUS1
PA-000.05193-US

24. (Original) The controller of claim 23, including programming for determining a plurality of the apparent electrical characteristic values and using the values to determine a relationship between a corresponding measured electrical characteristic and a condition of a tensile support.